

PRODUCT BRIEF:

CLOCK: GPU / MEMORY

- · Boost Clock*: TBD / TBD
- · Game Clock**: TBD / TBD

KEY SPECIFICATION

- · AMD Radeon™ RX 9070 XT GPU
- · AMD RDNA[™] 4 Architecture
- · 64 Compute Units (3rd Gen RT + 2nd Gen Al Accelerators)
- Microsoft® DirectX® 12 Ultimate
- · PCI[®] Express 5.0 Support
- · 2x 8-pin Power Connectors
- · 3x DisplayPort[™] 2.1a, 1x HDMI[™] 2.1b

KEY FEATURES

- Polychrome SYNC
- · Triple Fan Design
- · Stylish Metal Backplate
- · Striped Ring Fan
- · Reinforced Metal Frame
- · Air Deflecting Fin
- · Ultra-fit Heatpipe

AMD

· Super Alloy Graphics Card



AMD RADEON RX 9070 XT



//SRock

STEEL LEGEND

OLYCHROME SYNC





POLYCHROME SYNC

RADEON RX 9070 XT

Offers a comprehensive control to perform the built-in ARGB LEDs.



TRIPLE FAN DESIGN

Three fans for optimized cooling capacity.



STYLISH METAL BACKPLATE

Stylish metal backplate makes the graphics card fancy, cool and solid.



STRIPED RING FAN

Striped ring fan gets more lateral intake to provide better air ow.



AIR DEFLECTING FIN

Guide the airflow to go more regularly and quickly to enhance the cooling efficiency.



SPECIFICATION


ODB SILENT COOLING

Fans stop at low temperatures for complete silence.



ULTRA-FIT HEATPIPE

The heatpipes are consolidated to maximize the contact between them.



REINFORCED METAL FRAME

Enhances the structure to prevent the PCB from being bent.



LED SWITCH

Switch not only the build-in ARGB LEDs but also the connected ARGB devices at once.



Graphics Engine	AMD Radeon™ RX 9070 XT	Resolution	Digital Max Resolution:
Bus Standard	PCI [®] Express 5.0 x16		7680 x 4320
DirectX	12 Ultimate	Interface	3x DisplayPort™ 2.1a
OpenGL	4.6		1x HDMI [™] 2.1b
Video Memory	TBD	Recommended PSU	800 W
Engine Clock	Boost Clock*: TBD	HDCP Support	Yes
	Game Clock**: TBD	Multi-view	4
		Power Connector	2x 8-pin
Stream Processors	4096	Accessories	1x Quick Installation Guide
Memory Clock	TBD	Dimensions	298 x 131 x 58 mm, 2.9-slot
Memory Bus	TBD	Weight	1155 g



Product images for reference only. Product specifications may not be exactly as shown, please confirm specifications with your dealer prior to purchase. The brand and product names are registered trademarks of respective companies. For detailed product information, please visit our website.



* Boost Clock is the maximum frequency achievable on the GPU running a bursty workload. Boost clock achievability, frequency, and sustainability will vary based on several factors, including but not limited to: thermal conditions and variation in applications and workloads.

** Game Clock is the expected GPU clock when running typical gaming applications, set to typical TGP (Total Graphics Power). Actual individual game clock results may vary.

©AMD, the AMD Arrow logo, FidelityFX, FreeSync, Infinity Cache, Radeon, RDNA, and combinations thereof are trademarks of Advanced Micro Devices, Inc. DirectX and Windows are registered trademarks of Microsoft Corporation in the US and other jurisdictions. PCI Express is a registered trademark of PCI-SIG Corporation. HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing, LLC in the United States and other countries. Vulkan and the Vulkan logo are trademarks of the Khronos Group Inc. PID# 22166206-A



ASROCK EUROPE B.V. Bijsterhuizen 11-11 6546 AR Nijmegen The Netherlands ASROCK AMERICA, INC. 13848 Magnolia Ave, Chino, CA91710 U.S.A.

4F., No.37, Sec. 2, Jhongyang S. Rd., Beitou District, Taipei City 112, Taiwan (R.O.C.)