



# Z890 TAICHI LITE



## PRODUCT BRIEF :

- Supports Intel® Core™ Ultra Processors (Series 2) (LGA1851)
- 20+1+2+1+1 Power Phase, 110A SPS for VCore
- 4 x DDR5 DIMMs
- Supports Dual Channel, up to 9200+ (OC)
- 1 PCIe 5.0 x16, 1 PCIe 4.0 x16
- Graphics Output Options: 1 HDMI, 2 Thunderbolt™ 4 Type-C
- Realtek ALC4082 5.1 CH HD Audio Codec, ESS SABRE9219 DAC, WIMA Audio Cap, Nahimic Audio
- 4 SATA3
- 1 Blazing M.2 (PCIe Gen5 x4)
- 4 Hyper M.2 (PCIe Gen4 x4)
- 1 Hyper M.2 (PCIe Gen4 x4 & SATA3)
- 2 Thunderbolt™ 4 Type-C (Rear)
- 1 USB 3.2 Gen2x2 Type-C (Front)
- 4 USB 3.2 Gen2 Type-A (Rear)
- 8 USB 3.2 Gen1 (4 Rear, 4 Front)
- 6 USB 2.0 (2 Rear, 4 Front)
- 5Gbps LAN, 2.5G LAN
- 802.11be Wi-Fi 7 + Bluetooth
- Supports Memory OC Shield, BIOS Flashback 20K Caps with 1000uF Capacitance

I/O OVERVIEW



<h3>20+1+2+1+1 Power Phase Design</h3> <p>Vcore with SPS design, Delivering smoother and neater power to the CPU.</p>	<h3>Deluxe 6*M.2 Sockets</h3> <p>Supports up to 6*NVMe M.2 SSDs and one of which is able to accommodate the latest PCI Express 5.0 standard.</p>	<h3>Dual Thunderbolt™ 4 Type-C</h3> <p>It enables lightning-fast data transfer up to 40Gbps and connects versatile devices with a single Thunderbolt™ 4 cable.</p>	<h3>802.11be</h3> <p>20K Caps with 1000uF Capacitance</p>
<h3>Memory OC Shield (Patent Pending)</h3> <p>ASRock's exclusive Memory OC Shield effectively absorbs EMI noise, enhancing memory overclocking performance and stability.</p> <p>*Patent applied number: 113209060</p>	<h3>Toolless Multi-Layer M.2 Heatsink</h3> <p>Including a quick-release mechanism heatsink for effortless and toolless M.2 SSD installation.</p>	<h3>Optimized 5Gbps LAN (Patent Pending)</h3> <p>Featuring exclusive patented design with EMI resistance, surge protection, and noise filtering for a better networking experience.</p>	<h3>BIOS FLASHBACK</h3> <h3>SERVER-GRADE 8-LAYER PCB</h3>



# Z890 TAICHI LITE



## DETAIL SPECIFICATION

Platform	- ATX Form Factor: 12.0-in x 9.6-in, 30.5 cm x 24.4 cm - 8 Layer PCB - 2oz Copper PCB	USB	CPU: - 2 x Thunderbolt™ 4 Type-C (Rear) Chipset: - 1 x USB 3.2 Gen2x2 Type-C (Front) - 4 x USB 3.2 Gen2 Type-A (Rear) - 8 x USB 3.2 Gen1 (4 Rear, 4 Front) - 6 x USB 2.0 (2 Rear, 4 Front) * All USB ports support ESD Protection
Unique Feature	Superb Productivity - PCIe Gen5 (Graphics, M.2) - Dual Channel DDR5 - Thunderbolt™ 4 Type-C Ports (40 Gb/s) Rock-Solid Durability - Server-Grade Low-Loss PCB - 20+1+2+1+1 Power Phase, 110A SPS for VCore with Enlarged Heatsink Armor - Memory OC Shield - Flexible Integrated I/O Shield - 20K Long-lasting Black Caps (high quality and conductive polymer capacitors) Ultrafast Connectivity - 5G LAN, 2.5G LAN, 802.11be Wi-Fi 7 Module - ASRock Lightning Gaming Ports EZ Update - BIOS Flashback Button - ASRock Auto Driver Installer	Rear Panel I/O	- 2 x Antenna Ports - 1 x HDMI Port - 1 x Optical SPDIF Out Port - 2 x Thunderbolt™ 4 Type-C Ports (40 Gb/s for USB4 protocol; 40Gb/s for Thunderbolt protocol)* - 4 x USB 3.2 Gen2 Type-A Ports (10 Gb/s)** - 4 x USB 3.2 Gen1 Ports** - 2 x USB 2.0 Ports - 2 x RJ-45 LAN Ports - 1 x Clear CMOS Button - 1 x BIOS Flashback Button - 1 x Line Out Jack (Gold Audio Jack) - 1 x Microphone Input Jack (Gold Audio Jack) * Supports USB PD 3.0 up to 5V@3A (15W) charging ** USB32_56 are Lightning Gaming Ports. USB32_34 support Ultra USB Power.
CPU	- Supports Intel® Core™ Ultra Processors (Series 2) (LGA1851RL-ILM) - Supports Intel® Hybrid Technology - Supports Intel® Turbo Boost Max 3.0 Technology - Supports Intel® Thermal Velocity Boost (TVB) - Supports Intel® Adaptive Boost Technology (ABT) - Integrated NPU for dedicated AI acceleration - Supports ASRock Hyper BCLK Engine	Storage	CPU: - 1 x Blazing M.2 Socket (M2_1, Key M), supports type 2280 PCIe Gen5x4 (128 Gb/s) mode* - 1 x Hyper M.2 Socket (M2_2, Key M), supports type 2260/2280 PCIe Gen4x4 (64 Gb/s) mode* Chipset: - 1 x Hyper M.2 Socket (M2_3, Key M), supports type 2230/2242/2260/2280 SATA3 6.0 Gb/s & PCIe Gen4x4 (64 Gb/s) modes* - 1 x Hyper M.2 Socket (M2_4, Key M), supports type 2260/2280 PCIe Gen4x4 (64 Gb/s) mode* - 1 x Hyper M.2 Socket (M2_5, Key M), supports type 2260/2280 PCIe Gen4x4 (64 Gb/s) mode* - 1 x Hyper M.2 Socket (M2_6, Key M), supports type 2260/2280 PCIe Gen4x4 (64 Gb/s) mode* - 4 x SATA3 6.0 Gb/s Connectors  * Supports Intel® Volume Management Device (VMD) * Supports NVMe SSD as boot disks * If PCIe2 is occupied, M2_4 will be disabled.
Chipset	- Intel® Z890	RAID	- Supports RAID 0, RAID 1, RAID 5 and RAID 10 for SATA storage devices - Supports RAID 0, RAID 1, RAID 5 and RAID 10 for M.2 NVMe storage devices
Memory	- Dual Channel DDR5 Memory Technology - 4 x DDR5 DIMM Slots - Supports DDR5 non-ECC, un-buffered memory up to 9200+(OC)* 1DPC 1R Up to 9066+ MHz (OC), 5600 MHz Natively. 1DPC 2R Up to 6800+ MHz (OC), 5600 MHz Natively. 2DPC 1R Up to 6800+ MHz (OC), 4800 MHz Natively. 2DPC 2R Up to 5800+ MHz (OC), 4400 MHz Natively. - Max. capacity of system memory: 256GB - Supports Intel® Extreme Memory Profile (XMP) 3.0x * Please refer to Memory Support List on ASRock's website for more information. ( <a href="http://www.asrock.com/">http://www.asrock.com/</a> )	Connector	- 3 x Thermistor Cable Headers - 1 x SPI TPM Header - 1 x Power LED and Speaker Header - 1 x RGB LED Header* - 3 x Addressable LED Headers** - 2 x CPU Fan Connector (4-pin) (Smart Fan Speed Control)*** - 4 x Chassis Fan Connectors (4-pin) (Smart Fan Speed Control)*** - 1 x AIO Pump Fan Connector (4-pin) (Smart Fan Speed Control)*** - 1 x Water Pump Fan Connector (4-pin) (Smart Fan Speed Control)*** - 1 x 24 pin ATX Power Connector (Hi-Density Power Connector) - 2 x 8 pin 12V Power Connectors (Hi-Density Power Connector) - 1 x Front Panel Audio Connector (15u Gold Audio Connector) - 2 x USB 2.0 Headers (Support 4 USB 2.0 ports) - 2 x USB 3.2 Gen1 Headers (Support 4 USB 3.2 Gen1 ports) - 1 x Front Panel Type C USB 3.2 Gen2x2 Header (20 Gb/s) - 1 x Dr. Debug with LED - 1 x Power Button with LED - 1 x Reset Button with LED * Supports in total up to 12V/3A, 36W LED Strip ** Supports in total up to 5V/3A, 15W LED Strip *** CPU_FAN1 supports the fan power up to 1A (12W). *** CPU_FAN2, CHA_FAN1~4, AIO_PUMP and W_PUMP support the fan power up to 3A (36W). *** CPU_FAN2, CHA_FAN1~4, AIO_PUMP and W_PUMP can auto detect if 3-pin or 4-pin fan is in use.
Expansion Slot	CPU: - 1 x PCIe 5.0 x16 Slot (PCIe1), supports x16 mode* Chipset: - 1 x PCIe 4.0 x16 Slot (PCIe2), supports x4 mode* - 1 x M.2 Socket (Key E), supports type 2230 WiFi/BT PCIe WiFi module  * PCIe1 supports PCIe riser cards to extend one x16 slot to x8/x8 or x8/x4/x4 slots. * If PCIe2 is occupied, M2_4 will be disabled. * Supports NVMe SSD as boot disks	Graphics	* Intel® UHD Graphics Built-in Visuals and the VGA outputs can be supported only with processors which are GPU integrated. - Intel® X® LPG Graphics Architecture - 1 x HDMI 2.1 TMDS/FRL 8G Compatible, supports HDR, HDCP 2.3 and max. resolution up to 4K 120Hz - 2 x Intel® Thunderbolt™ 4, support HDCP 2.3 and max. resolution up to 8K 60Hz / 5K 120Hz* * Supports two 4K displays or one 8K display * Only the CPU's embedded graphics can be displayed through Thunderbolt ports. If you want to display to a Thunderbolt monitor, please use CPU models with embedded graphics.
Audio	- 5.1 CH HD Audio with Content Protection (Realtek ALC4082 Audio Codec) - WIMA Audio Capacitors (For Rear Outputs) - ESS SABRE9219 DAC for Rear Panel Audio (130dB SNR) - Individual PCB Layers for R/L Audio Channel - Direct Drive Technology on Front headphone port (Supports up to 600 Ohm headsets) - Nahimic Audio	BIOS Feature	- 256Mb AMI UEFI Legal BIOS with GUI support
LAN	1 x 5 Gigabit LAN 10/100/1000/2500/5000 Mb/s (Realtek RTL8126-VB) 1 x 2.5 Gigabit LAN 10/100/1000/2500 Mb/s (Dragon RTL8125BG) - Supports Dragon 2.5G LAN Software - Smart Auto Adjust Bandwidth Control - Visual User Friendly UI - Visual Network Usage Statistics - Optimized Default Setting for Game, Browser, and Streaming Modes - User Customized Priority Control	Software and UEFI	Software - ASRock Motherboard Utility (A-Tuning) - ASRock Polychrome SYNC - ASRock Dragon 2.5G LAN Software * These utilities can be downloaded from ASRock Live Update & APP Shop.  UEFI - ASRock EZ Mode - ASRock Full HD UEFI - ASRock My Favorites in UEFI - ASRock Auto Driver Installer - ASRock Instant Flash
Wireless LAN	- 802.11be 2x2 Wi-Fi 7 Module - Supports IEEE 802.11a/b/g/n/ac/ax/axe/be - Supports 2.4GHz/5GHz/6GHz* frequency band - Supports 320MHz channel bandwidth with 6GHz* frequency band * Wi-Fi 7 (6GHz band) will be supported by Microsoft® Windows® 11. The availability will depend on the different regulation status of each country and region. It will be activated (for supported countries) through Windows Update and software updates once available. - 1 antenna to support 2 (Transmit) x 2 (Receive) diversity technology - Supports Bluetooth 5.4 - Supports MU-MIMO	OS	- Microsoft® Windows® 11 64-bit
		Certifications	- FCC, CE - ErP/EuP ready (ErP/EuP ready power supply is required) - CEC Tier II ready
		Accessories	- 4 x SATA Data Cables - 1 x ASRock WiFi 2.4/5/6 GHz Antenna - 1 x ARGB Splitter Cable - 3 x Thermistor Cables - 2 x Screws for M.2 Sockets - 2 x Standoffs for M.2 Sockets